

DIGIMIC®

BRÄHLER ICS is committed to continually improving its products and so reserves the right to make technical modifications without notice

Microphone Stand

Microphone stand with built-in loudspeaker, connector socket for conference microphones TM55/TM7, pushbutton for Floor Request/Cancel Floor Request and Microphone On/Off or Microphone On; LED for Floor Request Acknowledgement and Microphone Live, 2.5m. permanently attached cable with connector, connector socket for additional microphone stands.

Technical Data

Corresponds to intern. standard IEC 914

Equipped with microphone pre-amplifier and loudspeaker, volume control via control console

Pushbutton for Floor Request/Cancel Floor Request and Microphone On/Off or Microphone On; LED for Floor Request Acknowledgement and Microphone Live

Coding switch for programming microphone numbers from 002 to 999

Connecting cable: permanently attached, length 2.5m, equipped with pin-connector, standard S8G

Connector socket for additional microphone stands, standard S8G; connector socket for gooseneck microphone: lock-type, standard R7

Dimensions: 110x174x33/52mm;
Weight including cable: 705g;
Colour: matt finish, black

Preferential Service Program

This item is available at short-notice.

DC/5



Conference Microphone

Electret microphone with ring-shaped indicator to show when microphone is live, rigid microphone neck with a short gooseneck articulation and lock-type connector, matt finish, black.

Technical Data

Corresponds to intern. standard IEC 914

Transducer principle: electret condenser

Acoustic operating principle: pressure gradient microphone

Pick-up characteristic: cardioid

Frequency response: 100 to 12,500Hz

Sensitivity: 7.5millivolt/pascal = -42dBV

Max. supply voltage: 10 volts

Connector standard: R7

Dimensions of microphone:
length 55mm, diameter 14mm;
dimensions of gooseneck:
length 265mm, diameter 7mm

Total length including connector:
360mm; colour: matt finish, black;
weight: 105g

Accessories

windscreen

Preferential Service Program

This item is available at short-notice.

TM56/5

