

DIGIMIC® classic

Under table installation box - UTM



WPF05-0110E.101215 BRÄHLER ICS is committed to continually improving its products and so reserves the right to make technical modifications without notice.

Description

In combination with a customized front panel the under table installation box CMic UTM is used as a microphone unit within the DIGIMIC system.

The front panel is equipped with an illuminated microphone ON / OFF button and a built-in microphone connector.

Optional a connection for headphones with corresponding volume control are installable. Alternatively or in addition, speakers may be installed for decentralised sound.

The units will be connected with one single cable for voltage supply, audio and control signals (Daisy Chain).

CMic UTM is integrated into all components of the DIGIMIC system.

The box can be mounted anywhere under the conference table. Therefore also particularly slim faceplate constructions can be realized.

Technical Data

The CMic UTM complies with international standard IEC914

Connectors

- **PREVIOUS (S8G)**
Female connector socket to connect further delegate units
- **NEXT (S8G)**
Male connector socket to connect next delegate units
- **Operating controls (D-Sub25)**
Connector socket to connect the operating controls/front plate

Equipment panel

- Illuminated microphone button for indication MIC ON/OFF, REQUEST
- Microphone connector (Minicon)

Options for front panel

- Two integrated loudspeakers for decentralized audio amplification
- Headphone socket with volume control

Digital Audio

- high quality digital audio:
Sample Rate: 48 kHz
Frequency response: 20 - 20,000 Hz
- Latency time: approx. 1ms microphone signal

Housing

- W x H x D: (164 x 29 x 172) mm
approx. (6.45 x 1.14 x 6.77) inch
- Custom front panel (for more information please contact Brähler ICS)

Other system components

- **CMic** Delegates' Conference Unit classic
- **CChair** Chairpersons' Conference Unit classic
- **DMic** Delegates' Conference Unit with data interface for DDoc
- **DChair** Chairpersons' Conference Unit with data interface for DDoc
- **DDoc** Docking Unit for expansion of DChair and DMic to a wireless conference unit
- **TMD/01** Conference Microphone with ring-shaped live indicator and integrated windshield functionality, gooseneck
- **S8G** Connection cable in different length